



## Contents

<b>00 - Technical data</b>	<b>1</b>
<b>1 Safety information</b>	<b>1</b>
1.1 Safety measures when working on vehicles with a start/stop system	1
1.2 Safety precautions when using testers and measuring instruments during a road test	1
<b>2 Identification</b>	<b>2</b>
2.1 Identification of final drive	2
<b>3 Repair notes</b>	<b>3</b>
3.1 General repair instructions	3
3.2 Rules for cleanliness	4
3.3 Gaskets, seals	4
3.4 Nuts and bolts	5
3.5 Pipe/wire routing and attachment	5
3.6 Notes on performance test	5
<b>4 Technical data</b>	<b>6</b>
4.1 Allocation final drive - engine	6
4.2 Capacities	6
<b>39 - Final drive - differential</b>	<b>8</b>
<b>1 Final drive</b>	<b>8</b>
1.1 Removing and installing final drive	8
<b>2 Assembly mountings</b>	<b>13</b>
2.1 Assembly overview - assembly mountings	13
2.2 Removing and installing bonded rubber bush on rear final drive	14
2.3 Removing and installing bonded rubber bush on rear gearbox carrier	19
<b>3 Gear oil</b>	<b>26</b>
3.1 Checking gear oil level	26
<b>4 High performance oil for all-wheel drive coupling</b>	<b>29</b>
4.1 Checking fluid level in all-wheel drive coupling	29
4.2 Draining and replenishing high performance oil for all-wheel drive coupling	30
<b>5 Oil seals</b>	<b>34</b>
5.1 Renewing right seal	34
5.2 Renewing left seal	39
5.3 Renewing input shaft seal	44
<b>6 Differential lock</b>	<b>47</b>
6.1 Function of differential lock	47
6.2 Components of differential lock	47
6.3 Removing and installing actuator for differential lock	48
6.4 Renewing bellows on rear final drive	50
<b>7 All-wheel drive coupling</b>	<b>52</b>
7.1 Assembly overview - all-wheel drive coupling	52
7.2 Checking function	54
7.3 Removing and installing pump for all-wheel drive coupling	54
7.4 Removing and installing all-wheel drive coupling	57
7.5 Removing and installing control unit	60
<b>8 Propshaft</b>	<b>62</b>
8.1 Assembly overview – propshaft	62
8.2 Removing and installing propshaft	64
8.3 Removing and installing centre propshaft bearing	73
8.4 Checking constant velocity joint	79